

swingo® 755E

Preparation



1 Ensure the machine is unplugged! Check the mains cable for damage. If cable is damaged do not use the machine!!!



2 Fill solution tank with clean water.




3 Dose cleaning product into dosing aid, then pour it into the solution tank.




4 Mount squeegee (position pockets of the squeegee exactly under the squeegee holder and push holder down).




5 Position tool(s) carefully under lifted brush unit.




6 Plug in mains cable.



7 Turn the machine on.



8 Lower brush unit with foot pedal. The brush will then be coupled automatically.



9 Start vacuum motor and solution supply (press orange buttons).



10 Adjust solution flow. (with blue lever)



11 Lower squeegee with squeegee lever.



12 Clean the floor.

Maintenance



13 Turn the machine off and unplug the cable.



14 Drain recovery tank and rinse with fresh water, then drain solution tank.



15 Remove the floating unit (filter and floater) with a rotation of the yellow filter in anticlockwise direction.



16 Clean the floating unit under running water and put it back into machine.



17 Clean solution filter and put it back into machine.



18 Remove tools, clean tools and allow to air dry.



19 Remove and clean squeegee.



20 Wipe machine with moist cloth.



21 Flip dosing aid.



22 Store machine with partially open lid (lid rests on dosing aid) for ventilation.

ATTENTION!

Do not use the machine before you have read and understood the operating instructions!
Questions: 1-800-558-2332

